























## PLUG CONFIGURATIONS

PLUG	PART #	TYPE	FREQ	AMP	VOLT	PLUG	PART #	TYPE	FREQ	AMP	VOLT	
		EZ-5-15P	NEMA	60	15	110-125		EZ-70141-HD	Schuko Plug Euro Standard	50	16	200-250
		EZ-6-15P	NEMA	60	15	200-250		EZ-999-21000	2P+E 110V SPLASHPROOF IP4	50	16	100-130
		EZ-5-20P	NEMA	60	20	200-250		EZ-999-21001	2P+E 240V SPLASHPROOF IP4	50	16	200-250
		EZ-L5-15P	NEMA Twistlock	60	15	200-250	<b>ATEX Certified Plugs</b>					
		EZ-L5-20P	NEMA Twistlock	60	20	110-125	<b>⊕ Power Component Substitution Warning</b>					
		EZ-L5-30P	NEMA Twistlock	60	30	110-125	Euramco Safety can install any specified plug or length of cord for your specific application however any modification will void the ATEX Certification of the unit.					
		EZ-L6-20P	NEMA Twistlock	60	20	200-250		EZ-ATX96430	ATEX Haz Loc Schuko Euro Standard ⊕	50/60	16	100-130
		EZ-L6-30P	NEMA Twistlock	60	30	200-250		EZ-ATX96433	ATEX Haz Loc Schuko Euro Standard ⊕	50/60	16	200-250
								EZ-UGP15231	Killark Haz Loc	60	15	125