



DESCO 960 PLUS

Trusted Body Fill

Desco 960 Plus is an economical body-fill grease designed to purge water and other contaminants from body cavities, and to protect valves from the damage and corrosion that occurs during storage and other site conditions. Recent formulation enhancements have improved resistance and metal adherence to deliver reliable protection and resistance across a wider temperature range.

Recommended Uses

Excellent for lubricating valves, post-hydrotesting, prior to storage or shipping.

Typical Characteristics

Appearance	Black, smooth
NLGI	2
Penetration (ASTM D217)	265-275
Worked Penetration, 60x (ASTM D217)	265-275
Base Oil	Mineral oil
Base Oil Viscosity	145 cSt at 40°C
Base Oil Pour Point	-10°F (-23°C)
Thickener	Inorganic
Additives	Antioxidant/corrosion inhibitor package
Solids Content	Graphite
Specific Gravity	0.9
Density (lb/gal)	7.8
Dropping Point (ASTM D566)	>500°F (260°C)
Flash Point	>440°F (227°C)
Temperature Range	-18°F to 350°F (-28°C to 177°C)

DO NOT USE ON OXYGEN SERVICE.
Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com